

## **CARBON WRAPS (UFMC, UFMC-S, AND UPAMC SERIES)**

**UFMC Series Synthetic Carbon Wraps** combine five micron barrier filtration with a polyester coconut-based carbon media. These filters significantly reduce chlorine, biofouling, and sediments found in well and municipal water sources. All components are FDA compliant, making them well-suited for water and food-based applications.

**UFMC-S Series Carbon Wraps**, identical to the UFMC Series, are cellulose-free and designed to remove sediment and organic compounds from industrial process solutions. Available in a variety of lengths and diameters, these filters have a stainless steel (SS) core and are a versatile, cost-effective, high-temperature option for today's market.

**UPAMC Series Cellulose Carbon Wraps** combine five-micron barrier filtration with coconut-based carbon. They are well suited for industrial and process applications where a reduction of fine particulates and organics are needed. Internal downstream media precludes possible media migration that may interfere with the process solution. UPAMC is not recommended for potable water applications due to the organic content of the cellulose media.



## CARBON WRAPS (UFMC, UFMC-S, AND UPAMC SERIES)

### ★ OVERVIEW

- **Type:** Polypropylene Netting
- **Construction (UFMC Series):**
  - Carbon Impregnated Polyester Media
  - Plastisol Molded Ends
  - 304SS (Stainless Steel) Core (UFMC-S Series Only)
- **Construction (UPAMC Series):**
  - Carbon Impregnated Cellulose Media
  - Plastic End Caps With EPDM Gaskets
- **Micron Rating:** FDA Polypro in 5 Microns
- **Maximum Temperature:** 180 °F (82 °C)



UPAMC

UFMC &amp; UFMC-S

### ★ SPECIFICATIONS

PART NUMBER	DIMENSIONS	REC. FLOW RATES	ODOR REDUCTION
UFMC-10	2.50" Ø x 10", 20", 30"	5 GPM @ 4 PSI	2,000 gal. @ 1 GPM/per 10"
UFMC-20	2.50" Ø x 10", 20", 30"	5 GPM @ 4 PSI	4,000 gal. @ 1 GPM/per 10"
UFMC-30	2.50" Ø x 10", 20", 30"	5 GPM @ 4 PSI	6,000 gal. @ 1 GPM/per 10"
UFMC-40	2.50" Ø x 10", 20", 30"	5 GPM @ 4 PSI	8,000 gal. @ 1 GPM/per 10"
UFMC-BB-10	4.50" Ø x 10", 20", 30"	8 GPM @ 5 PSI	15,000 gal. @ 4 GPM/per 10"
UFMC-BB-20	4.50" Ø x 10", 20", 30"	8 GPM @ 5 PSI	25,000 gal. @ 4 GPM/per 10"
UFMC-BB-30	4.50" Ø x 10", 20", 30"	8 GPM @ 5 PSI	35,000 gal. @ 4 GPM/per 10"

**Warning:** Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. After installation, it is recommended to flush the filter for at least twenty seconds prior to using water.



an enpress group company

For more information, visit [UnitedFilters.com](http://UnitedFilters.com) or email [Info@UnitedFilters.com](mailto:Info@UnitedFilters.com)

**UFI TEXAS PLANT:** 901 S. Grant St., Amarillo, TX 79101 / 806-373-8386 / 806-371-7783 (fax)

**UFI CALIFORNIA PLANT:** 7946 Ajay Dr., Sun Valley, CA 91352 / 818-504-9471 / 818-252-7476 (fax)

**ENPRESS GROUP:** 34899 Curtis Blvd., Eastlake, OH 44095 / 440-510-0108 / [ENPRESSgroup.com](http://ENPRESSgroup.com)

United Filters International® is a trademark of United Filters International. © United Filters International 2025 / 4/2025