

★ NOMENCLATURE—STRING WOUND FILTERS

U P 10 R 10 P V SOC BUN ISW L

U	STYLE
	U: Standard

P	MEDIA									
	R: Rayon (Viscose)	N: Nylon	G: Fiberglass	F: Fibrillated	K: Polyester					
	PDN: NSF42/61 Polypropylene	P: Industrial Polypropylene	PD: FDA Polypropylene	RT: Ryton	C: FDA Bleach Cotton					
	CCU: Industrial White Cotton	U: Natural Cotton								

10	MICRON									
	0.5	1	3	5	10	15	20	25	30	40
	50	75	100	125	150	200				

R	OUTSIDE DIAMETER									
	T: 2"	E: 2-1/4"	F: 2-3/8"	R: 2-1/2"	H: 2-5/8"	S: 2-3/4"	L: 2-7/8"	P: 3"	BB: 4"	J: 4-1/2"
	X: Special									

10	LENGTHS									
	5"	6"	7"	8"	9"	9.75"	10"	12"	12.50"	18"
	19.50"	19.75"	20"	29.50"	30"	36"	39"	40"	50"	60"
	70"	72"								

P	CORE MATERIAL				
	T: Tin-Plated Steel	P: Polypropylene	A: 316 Stainless Steel	S: 304 Stainless Steel	TW: Tin Steel Wild Cat
	SW: 304SS Wild Cat				

V	CORE COVER	
	No Symbol: None	V: Specific Core Cover

SOC	END TREATMENT				
	PM: Poly Cap & Metal Spring	06F: 226 O-Ring & Fin	06C: 226 O-Ring & Cap	SOC: 222 O-Ring & Cap	SOF: 222 O-Ring & Fin
	EC: Extended Crimped Core	(S)E: 316SS Insert	(P)E: Poly Core Insert	PS: Poly Spring	ACS: 3" Tin Cap & Spring
	CSA: Stad. 316SS Cap & Spring	[Blank]: No End Treatment—DOE			

NOTE: Only select an O-ring option if you selected a non-plastisol end treatment above.

BUN	O-RINGS			
	BUN: Buna	EPD: EPDM	VIT: Viton	SIL: Silicone

ISW	PACKAGING		
	ISW: Individual Shrink Wrap	IW: Individual Bag	[Blank]: Bulk Bagged

L	LABEL
	L: Individual Label

Contact factory for special lengths and configuration requests.

For more details and answers to specific compatibility questions, visit **UNITEDFILTERS.COM/COMPATIBILITY**

